	Type	Ref #	Hits	Search Text
67	BRS	S67	3279	(set$4 updat$3 chang$3) near4 (value parameter) same (motor driv$3) with (chang$3 mov$3) near5 (condition$3 stat$5 mode)
68	BRS	S68	984	(carriage print$4 head pen) with (speed$3 velocit$3) same (maximum minimum) adj3 value
69	BRS	S69	12	S67 and S68
70	BRS	S70	18680	detect$3 adj4 (condition$3 speed status state position) and (home rest$3 stationary) adj3 (position location)
71	BRS	S71	4222	static adj4 dynamic with (condition status mode state)
72	BRS	S72	43	S70 and S71
73	BRS	S73	61671	"347"/$.ccls.
74	BRS	S74	2	S73 and (S69 S72)
75	BRS	S75	6	S67 and S71

	DBs	Time Stamp	Comments	Error Definition
67	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:04		
68	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:06		
69	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:06		
70	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:09		
71	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:10		
72	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:10		
73	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:11		
74	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:13		
75	US-PGPUB; USPAT; EPO; JPO; DERWENT	2005/09/28 12:13		